



All★ Star Home - Building Checklist

Complete ALL sections and have contractor sign below. **PLEASE PRINT.**

Submit this checklist along with a completed copy of the All-Star Home Bonus Incentive form.

Last Name (Homeowner)		Address (Qualifying All-Star Home)		
City	State	Zip	Completion Date	

Enter installed insulation R-values for the following components that exist in the home. **If a component does not apply, enter NA.**

BUILDING COMPONENT		DESCRIPTION/REQUIREMENTS	Minimum Insulation R-value	Installed R-value
WALLS	Above Grade	Basement walls more than 50% above grade and the box sill of basement must also meet this requirement.	R-21	
	Below Grade	Basement walls more than 50% below grade.	R-10	
	Crawlspace Wall	Required for closed, non-vented crawlspaces.	R-20	
CEILINGS	All Ceiling Types		R-38	
FLOORS	Basement (non-heated floor)	Floor at least 4 feet below grade, otherwise treat as a Slab. For walkout basements see Walkout Slab.	None	NA
	Basement (heated floors)	Insulation required under floor. For walkout basements see Walkout Slab.	R-10	
	Slab	Floors less than 4 feet below grade. Insulation must cover face of slab with rigid foam that extends 4 feet below grade (a combination of vertical and horizontal distance can be used to meet requirement).	R-10	
	Walkout Slab	The edge of floor slab (walkout side) must be insulated with rigid foam extending 4 feet below grade (a combination of vertical and horizontal distance can be used to meet requirement); remaining floor area must still meet requirements for Basement floors.	R-10	
	Floor over Crawlspace	Required for open, non-vented crawlspaces.	R-30	

WINDOWS (Check below to verify requirements are met; provide window information)

- Must be low-E windows and meet Energy Star requirements with a U-value of 0.35 or less. At time of installation, windows should display the Energy Star label or NFRC (National Fenestration Rating Council) label showing the U-value.

Window Brand and Product Line: _____

Window Description: (example: vertical slider) _____

BUILDING LEAKAGE (Check measure used to to minimize infiltration of outdoor air)

- Exterior house wrap with all seams taped (eg. Tyvek paper)
- Exterior rigid board insulation (extruded polystyrene or urethane sheathing) with all seams taped
- Other (subject to approval). Describe: _____

Builder Information:

Homeowner or Builder Notes:

Business Name		
Address		
City	State	Zip Code

BUILDER AGREEMENT (Signature Required)	
I agree that all of the above information is true and that it represents the installed measures for the home located at the address shown. I understand that the Cooperative reserves the right to inspect the home to verify this information before issuing any rebates to the member.	
Builder Signature	Date